

Model	Dimensions	Min Speed	Max Speed	Min Blank Size	Max Blank Size
150 Servo HS	88.5" x 187"	15cpm	55cpm	5.875" x 27.3125" (150 x 700 mm)	27.5625" x 61.0625" (700 x 1550 mm)
170 Servo HS	91.875" x 194.75"	15cpm	40cpm	5.875" x 27.3125" (150 x 700 mm)	27.5625" x 68.3125" (700 x 1735 mm)
200 Servo	94" x 324.375" <i>(Elevator Loading Module Type)</i> 94" x 200" <i>(Standard Loading Type)</i>	5cpm	30cpm*	7.875" x 39.375" (200 x 1000 mm)	31.5" x 80.6875" (800 x 2050 mm)
200 Servo XL	195.625" x 310.25"	5 cpm	20cpm	11.4375" x 54.75" (290 x 1390 mm)	38.875" x 80.6875" (987 x 2050 mm)

*Loading Module Type and Blank Size will effect Speed

General Specifications

Air	90psi 15-35cfm dry air (Varies by model and speed)
Electric	480 Volts 30 or 60-amp service (May vary by model)
Adhesive	Nordson Pro Blue 7
HMI	Allen Bradley - Bosch - Dynics
PLC	Allen Bradley - Bosch



meta™ SYSTEMS

from

SMURFIT-STONE

Automated Packaging Systems

